Radiant*Black™
Double Overhead Warmers

Models: FDDB, FDDLB -18, -24, -30, -36, -42, -48, -54, -60, -66, -72

PRODUCT: QUANTITY: ITEM #:

Designed Smart

- New Radiant Black™ Overhead Warmers are constructed with a flat black panel that is heated with aluminum black anodized heating.
- Highly efficient “gentle” heat.
- Easy to install and customize to your operation.
- Thermostatically controlled system allows operator to “dial in” the optimal heat setting for food types.
- Produces an even level of heat at a very close distance to food.

Built Solid

Most Durable Overhead Warmers!

- Stainless Steel Construction resists corrosion, is easy to clean, and presents an attractive appearance.
- Continuous stainless steel housing is the strongest in the industry. Units will not sag or warp.
- Supplied with angle hanging brackets for optimal spacing from the overhead area and sturdiness.
- Polished stainless steel reflector behind aluminum heat plate focuses radiant energy back toward the heat emitter. This focuses energy toward food, not out of the back of the unit.

Reliability backed by APW Wyott’s Warranty

- 1 year parts and labor warranty
- Certified by the following agencies:

c UL us

UL SANITATION

PROTECTED BY APW WYOTT'S 1 YEAR LIMITED WARRANTY



*RADIANT*BLACK™ DOUBLE OVERHEADS*

APW Wyott Design Features

- Side-Mounted Control Box (standard) or remote control box.
- All models come standard with rocker switches with a built in pilot light and angle mounting brackets.

Options

- Chain Hanging Kits (75901) per foot
- Two Tubular Stands (76180)
- Remote Control 120V/208V/240V (70408273)
- Remote Control Lights 120V (70408273)
- Remote Control Lights 120/208V & 120/240V (70406273) 12” box

Consultant Specifications

The Ceramic Food warmer shall be a Radiant*Black™ manufactured by APW Wyott Foodservice Equipment Company, Dallas, TX 75226 U.S.A.

The food warmer shall be model..., rated at ...watts, ...volts, single phase and be ...inches (centimeters) in overall width.

The Radiant*Black™ shall consist of a stainless steel housing, polish mirror stainless steel reflectors, and require either a control box or remote control enclosure.

See reverse side for product specifications.

APW Wyott Foodservice Equipment Company · 729 Third Ave., Dallas, TX 75226
(800) 527-2100 · (214) 421-7366 · Fax (214) 565-0976 · www.apwwyott.com· info@apwwyott.com

Rev. 4/12/2004

Radiant*Black™
Double Overhead Warmers

Models: FDDB, FDDLB -18, -24, -30, -36, -42, -48, -54, -60, -66, -72

PRODUCT: QUANTITY: ITEM #:



Double Radiant*Black Overhead Warmers

Model	Length	Watts	Weight
FDDB-18	18"	800	12 lbs
FDDB-24	24"	1150	16 lbs
FDDB-30	30"	1520	18 lbs
FDDB-36	36"	1840	21 lbs
FDDB-42	42"	2200	24 lbs
FDDB-48	48"	2530	25 lbs
FDDB-54	54"	2850	28 lbs
FDDB-60	60"	3220	30 lbs
FDDB-66	66"	3600	34 lbs
FDDB-72	72"	3960	36 lbs

PRODUCT SPECIFICATIONS

Construction:

Radiant*Black™ Overheads are supplied with Stainless Steel Housing and control box. Aluminum black anodized aluminum plate. Polished mirror stainless steel reflectors behind aluminum plate. Unit is fully insulated with one inch insulation. Hanging Angle brackets are supplied.

Electrical Information:

Radiant*Black™ Overheads are supplied with a rocker switch that turns the power on and, for lighted units, one that turns on the lights. Standard Double unit sizes 42" and above are only available in 208V and 240V (Lighted unit is 120/208V or 120/240V). Can be ordered with standard side mounted box or remote control box (add R to the end of model number)

Double Lighted Radiant*Black Overhead Warmers

Model	Length	Watts	Weight
FDDLB-18	18"	880	13 lbs
FDDLB-24	24"	1230	17 lbs
FDDLB-30	30"	1600	19 lbs
FDDLB-36	36"	2000	22 lbs
FDDLB-42	42"	2360	25 lbs
FDDLB-48	48"	2690	26 lbs
FDDLB-54	54"	3010	29 lbs
FDDLB-60	60"	3460	31 lbs
FDDLB-66	66"	3840	35 lbs
FDDLB-72	72"	4200	37 lbs

Electrical Specifications:

- Available in 120V, 208V, 240V, 120V/280V, and 120V/240V
- Models FDDB-42 through FDDB-72 available only in 208V & 240V
- Models FDDLB-42 through FDDLB-72 available only in 120V/208V or 120V/240V.
- FDDLB-66 and FDDLB-72 are supplied with3 amp fuse, 30 amp circuit, and 12" remote(70416273)

Overall Dimensions:

Double units:	15 1/8" W x 2½" H
Side mounted box:	4 13/32" W x 2½"H x 8 1/8" L
Lighted double units:	15 1/8" W x 2½" H
Side mounted box:	4 13/32" W x 2½" H x 12 1/8" L

(See charts for individual lengths)

Shipping:

Freight class 92½
FOB: Dallas, TX

**APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.*